



# REMOTE MIXER SO-MIX-T-24V

## DESCRIPTION:

- Microphone and line level input
- Two inputs, one balanced output
- Individual volume control with joint bass and treble control
- Automatic mix with selectable Talkover function. 30dB, Talkover time: 3 seconds.

## OPTIONAL ACCESSORY:

- 2-Gang accessory wall plate: SO-MIX-PLATE
- AD-246 AC Adapter required



**Installation Note:** When using the Wall Plate (SO-MIX-PLATE) with the Remote Mixer (SO-MIX-T-24V) you must remove the plastic ring around the SO-MIX-T-24V. The input unit is attached by 2 magnets and can be easily removed. See image.



Wall Plate



With Wall Plate



AC Adapter

## SPECIFICATIONS:

Power Source	24 V DC
Output	0dBV
Power/Current Consumption	40mA
Input	Microphone XLR balanced input, Sensitivity -20/-40dBV
Output	Euroblock connector line level 0dBV
Phantom Power	24 V selectable
Tone Control	Bass: ±10 dB at 100 Hz, Treble: ±10 dB at 10 kHz
Operating Temperature	-10°C to +40°C (14°F to 104°F)
Finish	White
Dimensions	86 (W) × 86 (H) × 36 (D) mm (3.35" x 3.39" x 1.42")
Optional Accessory	2-gang wall plate SO-MIX-PLATE, AD-246 AC Adapter

TOA Canada Corporation  
[www.TOAcanda.com](http://www.TOAcanda.com) • 1-800-263-7639